LOW MAINTENANCE SEALER & FINISH

PRODUCT DESCRIPTION

If you need an easy-to-use solution for a glossy floor finish, Arrow's Low Maintenance Sealer & Finish will get results! Our solution is black mark and detergent resistant and quick drying with superior leveling properties and slip resistance. After drying, Low Maintenance Sealer & Finish forms a hard, durable, detergent-resistant layer that can withstand multiple daily damp mopping and retains shine after low/high speed buffing

Approximate Coverage: 2,000-2,500 square feet per gallon.

DIRECTIONS

See full label for complete directions.

Be sure the floor has been stripped, neutralized, dry and free of dust and debris. Use a new micro fiber or rayon mop. Apply very thin coats of finish. When applied correctly, drying time is 15-20 minutes. Be sure the floor is dry before applying additional coats. For optimum results, burnish with a regular or high speed buffer. To maintain the gloss and clarity of your newly finished floor, clean floor daily with a neutral cleaner.

PACKAGING

4/1 Gallon Case 5 Gallon Pail 55 Gallon Drum 275 Gallon Tote

SPECIFICATIONS

Physical State: Liquid

Color: White

Odor: Mild Polymer

pH: 8 - 9

Specific Gravity: 1.0 - 1.1

IDEAL FOR

Vinyl • Vinyl Asbestos • Asphalt • Tile • Sealed Terrazzo Concrete • Linoleum • Composition Tile • Wood



Arrow helps industry partners grow their business by delivering complete chemical solutions using a century of expertise in private brand and contract manufacturing.

FOR SALES SUPPORT PLEASE CALL

313.237.0277

or visit

arrowchemicalproducts.com





Product Code: 278