AROTHANE SEALER & FINISH

PRODUCT DESCRIPTION

Arothane Sealer & Finish from Arrow is a polyurethane and acrylic emulsion blend that delivers a superior gloss and extra durable protection. The formulation provides outstanding results with non-buffed as well as high speed and spray buffed floors. Easy to apply, maintain, re-coat, and strip, Arothane is the perfect choice for lay it and leave it jobs.

DIRECTIONS

See full label for complete directions.

Strip floors thoroughly (if used on new flooring, all factory finish must be removed). Rinse floors using a neutralizer and allow floor to dry completely.

Apply thin uniform coat of finish with a new rayon mop or appropriate applicator to floor finish. Let floor dry for at least 30-45 minutes between coats. This is a very high solids sealer/finish and will take longer to dry than traditional floor finish products.

For optimum results, apply 2-3 thin coats of Arothane. Additional coats may be applied for extra durability in high traffic areas and additional shine.

Never pour left over product back into container to avoid contamination.

PACKAGING

4/1 Gallon Case 5 Gallon Pail 55 Gallon Drum

SPECIFICATIONS

Physical State: Liquid

Color: White Odor: Mild pH: 8 9

Specific Gravity: 1.0 - 1.1

IDEAL FOR

Vinyl & Vinyl Asbestos • Terrazzo • Wood • Concrete Composition Tile • Painted Concrete



Arrow helps industry partners grow their business by delivering complete chemical solutions using a century of expertise in private brand and contract manufacturing.

FOR SALES SUPPORT PLEASE CALL

313.237.0277

or visit

arrowchemicalproducts.com





Product Code: 300