

NO RINSE WAX STRIPPER



Arrow helps industry partners grow their business by delivering complete chemical solutions using a century of expertise in private brand and contract manufacturing.

FOR SALES SUPPORT PLEASE CALL

313.237.0277

or visit

arrowchemicalproducts.com

SCAN FOR SDS



PRODUCT DESCRIPTION

Arrow's No Rinse Wax Stripper uses a powerful formula to cut through layers of old finish in minutes, reducing the labor time associated with conventional stripping products. Effective on various floor finishes including acrylic, metal crosslinked, co-polymer, styrene, and acrylic/urethane blends. Easily handles carnauba and microcrystalline waxes and acrylic or urethane sealers.

DIRECTIONS

See full label for complete directions.

Strip only a manageable area at one time.

Regular Stripping: 13 oz. per gallon of hot water.

Heavy Duty Stripping: 26 oz. per gallon of hot water.

For best results use a scrubbing machine with a black strip pad, or mop buckets and mops, and wet vac with squeegee.

Thoroughly saturate surface and allow to remain for about 5 minutes. Be sure the surface stays wet with stripper solution. Scrub floor surface. After scrubbing, pick up the solution with a wet vac and squeegee or mop and bucket. For best results, rinse with clear water or Neutralizer. When the floor is dry it is ready for re-coating.

PACKAGING

4/1 Gallon Case

5 Gallon Pail

55 Gallon Drum

SPECIFICATIONS

Physical State: Liquid

Color: Clear

Odor: Detergent

pH: > 13

Specific Gravity: 1.0 - 1.1

IDEAL FOR

Acrylic • Metal Crosslinked • Carnauba Wax • Acrylic Co-Polymer • Polymer • Microcrystalline Wax
Water-Based Urethanes • Styrene • Acrylic/Urethane Blends



Product Code: 312