

ZIPITY STRIP



Arrow helps industry partners grow their business by delivering complete chemical solutions using a century of expertise in private brand and contract manufacturing.

FOR SALES SUPPORT PLEASE CALL

313.237.0277

or visit

arrowchemicalproducts.com

SCAN FOR SDS



PRODUCT DESCRIPTION

Zipity Strip from Arrow uses a powerful formula to quickly strip multiple coats of burnished finish from resilient tile floors. The fast acting, labor saving solution works with hot or cold water and usually requires no scrubbing, reducing the time it takes to strip a floor! Delivers results on many floor finishes including polymer, co-polymer, acrylic, acrylic/urethane blends, styrene, and metal crosslinked. Easily tackles microcrystalline or carnauba waxes and urethane or acrylic sealers.

DIRECTIONS

See full label for complete directions.

1. For best results you will need a scrubbing machine with strip pad, mop buckets and mops, and a wet vac with squeegee.
2. Mix stripper in mop bucket at a dilution of 1 part stripper to 5 parts water. Thoroughly saturate floor surface and allow to remain for about 5 minutes. Be sure the surface stays wet with stripper solution.
3. Scrub floor surface with machine. In most cases, one pass with the scrubber will remove even the toughest finish build-ups.
4. After scrubbing, pick up the solution with a wet vac and squeegee. A mop or autoscrubber may also be used.
5. Mop the floor with a clear water solution. When the floor is dry it is ready for recoating.

PACKAGING

4/1 Gallon Case

5 Gallon Pail

55 Gallon Drum

SPECIFICATIONS

Physical State: Liquid

Color: Clear

Odor: Detergent

pH: 11.5 - 13.5

Specific Gravity: 0.95 - 1.05

IDEAL FOR

Acrylic • Metal Crosslinked • Carnauba Wax • Co-Polymer Polymer • Microcrystalline Wax • Water-Based Urethanes
Styrene • Acrylic/Urethane Blends



Product Code: 313